OTP

Model No. JW-AP33



SPECIFICATIONS

	OTP
	OTP
	OTP

OTP, OTP, , , OTP, OTP, , OTP, , , OTP,

OTP horizontal mode
High precision and durable

Mold general

Suitable for a variety of molds, widely used







Horizontal mode





Vertical mode





Single grain

Mold general

Suitable for a variety of molds, widely used







Horizontal mode





Vertical mode





Single grain





OTP straight mold

Model: OTP straight mold
Weight: 4.5KG
Feeding block: 35mm
Slider stroke: 30mm
Die knife adjustment: scale rotary
Process type: stamping mould
Main processing equipment: terminal crimping
Provide customized processing: Yes

OTP single grain mold

Model: OTP single grain mold
Weight: 4.5KG
Feeding block: 35mm
Slider stroke: 30mm
Die knife adjustment: scale rotary
Process type: stamping mould
Main processing equipment: terminal crimping
Provide customized processing: Yes





Single U-shaped mold

Model: Single U-shaped mold

Weight: 4.5KG

Feeding block: 35mm

Slider stroke: 45mm

Die knife adjustment: scale fine adjustment

OTP U mold



Model: OTP U-shaped mold

Weight: 4.5KG

Feeding block: 25mm

Slider stroke: 30mm

Die knife adjustment: scale rotary

Process type: stamping mould

Main processing equipment: terminal crimping

Provide customized processing: Yes



Flag model

Model: Flag mold


Weight: 6.5KG

Feeding block: 25mm

Slider stroke: 30mm

Die knife adjustment: scale fine adjustment

2000#mold



Model: 2000#mold

Weight: 5.2KG

Feeding block: 35mm


Slider stroke: 40-48mm

Die knife adjustment: scale rotary

Process type: stamping mould

Main processing equipment: terminal crimping

Provide customized processing: Yes



Plastic mould

Model: Plastic with mold

Weight: 4.5KG

Feeding block: 35mm

Slider stroke: 30mm

Die knife adjustment: scale rotary

Process type: stamping mould

Main processing equipment: terminal crimping

Provide customized processing: Yes

OTP high precision horizontal mold



Feeding method: horizontal feed
Feeding stroke: 30mm
Slider stroke: 30mm
Scope of application:
It is suitable for high-precision terminal and connection wire manufacturers with very high requirements for crimping. The ingredients are QPQ and heat-treated fine embroidery technology, which can make the product size more accurate, and it is common with JAM, Xinming and terminal machines.



4S-40 pneumatic horizontal die

Feeding stroke: 40mm
Slider stroke: 40mm
Scope of application: suitable for European and American series automatic and semi-automatic crimping equipment, C.H/I.H adjustment accuracy is 0.02mm, suitable for various horizontal terminals

4E-40 pneumatic straight mold



Feeding stroke: 40mm
Slider stroke: 40mm
Scope of application: suitable for European and American series automatic and semi-automatic crimping equipment, C.H/I.H adjustment accuracy is 0.02mm, suitable for various straight terminals



4S-30 pneumatic horizontal die

Feeding stroke: 40mm
Slider stroke: 30mm
Scope of application: It is suitable for Japanese series automatic and semi-automatic crimping machines and domestic 30-stroke terminal machines. The crimping knife is common with OTP, and the C.H/I.H adjustment accuracy is 0.02mm.

4E-30 mechanical straight mold



Feeding method: direct delivery
Feeding stroke: 30mm
Slider stroke: 30mm
Scope of application: suitable for automotive terminals, can be used for conventional terminal machines, fine-tuning single grid is 0.02mm, large adjustable range, high precision.



JST horizontal mode

Feeding method: horizontal feed
Feeding stroke: 30mm
Slider stroke: 40mm
Scope of application: suitable for JST automatic terminal machine and hand punching machine.

JST straight mold

Feeding method: direct delivery
Feeding stroke: 30mm
Slider stroke: 40mm
Scope of application: Suitable for JST automatic terminal machine and 40 stroke terminal machine.






JST flag mold

Feeding method: direct delivery
Feeding stroke: 30mm
Slider stroke: 40mm
Scope of application: 187/205/250 flagship terminal matching mold, 40 stroke terminal machine.

4TS precision horizontal mold



Feeding method: horizontal feed
Feeding stroke: 40mm
Slider stroke: 30mm
Scope of application: suitable for all kinds of large-stroke terminals, the large and fine adjustment is 0.025mm, the small and fine adjustment is 0.15mm, the upper knife width is 26mm, and the lower knife width is 30mm. Suitable for conventional terminal machines.



4TE precision straight mold

Feeding method: direct delivery
Feeding stroke: 40mm
Slider stroke: 30mm
Scope of application: suitable for all kinds of large-stroke terminals, the large and fine adjustment is 0.025mm, the small and fine adjustment is 0.15mm, the upper knife width is 26mm, and the lower knife width is 30mm. Suitable for conventional terminal machines.




Conventional Dotting Die

Slider stroke: 30mm
Scope of application: 1.5mm~6mm tube type dotting on all sides, pressure point width 2mm~6mm.

Heavy Dotting Mold

Slider stroke: 30mm
Scope of application: 6mm~16mm tube type terminals are dotted on all sides, and the dot width is 4-10mm. The terminal machine needs a terminal machine of more than 4 tons.





Pneumatic super wide transverse die

Feeding stroke: 50mm
Slider stroke: 30mm
Scope of application: Mainly for 60mm~ 100mm ultra-wide special terminals. The blades are common to OTP blades, and special terminal machine return seats are required.

Pneumatic automatic machine super wide horizontal di



Feeding stroke: 50mm
Slider stroke: 30mm
Scope of application: 40mm~60mm ultra-wide terminals, which can be used for automatic terminal machines and ordinary terminals The machine, blade and OTP die are common.



European single die

Slider stroke: 40mm
Scope of application: Suitable for various bulk terminal vibration plate feeding, used in European and American automatic crimping machines and semi-automatic crimping machines.