□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□1.3 □□□WPM-5ND

Model No. WPM-5ND



SPECIFICATIONS

□□□□□	WPM-5ND
□□□□□□□□□□□□□□□□□□□□

[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	1.3 T
[illegible]	⩽ 16 mm²
[illegible]	⩽ 6 mm²
[illegible]	⩽ 35 mm²
[illegible]	0.4–1 MPa
[illegible]	260 × 120 × 140 mm
[illegible]	4 kg

[illegible]


— [illegible] [illegible] 0.5–2.5 mm² [illegible]

— [illegible] [illegible] 4–16 mm² [illegible]

— [illegible] [illegible] 6 mm² [illegible]

— [illegible] [illegible] 35 mm² [illegible]

— [illegible]







Air Connection

The machine and foot pedal connected to the corresponding hole,convenient and safe



Replaceable Jaws

Easy change to different size wire dies , meet various crimping needs



Foot Pedal Design

The crimping effect is more accurate and convenient



FAQ

WPM-5ND

WPM-5ND 1.3 (1.3T) 35mm²

35mm²

WPM-5ND

WPM-5ND

WPM-5ND

WPM-5ND 1.3T