WPM-5030

Model No. WPM-5030



SPECIFICATIONS

	WPM-5030
	0.2-2.5
	0.1-10
	±0.02
	40
	3.0T
	220V / 110V / 50 / 60 Hz

WPM-5030 0.2-2.5 mm2 0.1-10 mm ±0.02 mm 40 mm 3.0 T 220 V 110 V 50/60 Hz

WPM-5030

WPM-5030 ±0.02 mm

1. 0.2-2.5 mm2 0.1-10 mm
2. ±0.02 mm 40 mm
3. 3.0 T
4.
5. HMI
6. 220 V / 110 V, 50/60 Hz

	WPM-5030
	0.2-2.5 mm2
	0.1-10 mm

[illegible]	[illegible]
[illegible]	±0.02 mm
[illegible]	40 mm
[illegible]	3.0 T
[illegible]	220V / 110V, 50/60 Hz
[illegible]	[illegible]

[illegible]

— [illegible]: [illegible]0.2-2.5 mm2

— [illegible]: [illegible]

— [illegible]: [illegible]

— [illegible]: [illegible]

— [illegible]: [illegible]







Vibrating Plate

The waterproof plug is automaticly placed on the guide rail.



Applicator/mold

High precision customized applicator for quality crimping assurance.



Waterproof Bolt Device

Auto feed waterproof seals with easy changeable feeding tracks for different sizes of seal applications.

Product Images



FAQ

WPM-5030 Semi-Automatic Wire Stripping Seal Crimp Machine

WPM-5030

WPM-5030

WPM-5030 0.2 mm² 2.5 mm²

WPM-5030

(WPM-5030

WPM-5030

WPM-5030